

Declaration of Performance DoP: 500113CPR-29-03-2021

- 1. Unique identification code of the product-type: Treskrue XLNT
- **2.** Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4): **Treskrue XLNT**

| Itemnumber | GTIN | Dimension |
|------------|---------------|-----------|
| 500113 | 7034355001132 | 4,5x30 |
| 500114 | 7034355001149 | 4,5x40 |
| 500115 | 7034355001156 | 4,5x50 |
| 500116 | 7034355001163 | 4,5x60 |
| 500117 | 7034355001170 | 4,5x70 |

Material: Stainless steel A4

- **3.** Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification: **for structural timber products.**
- 4. Name, reg. trade name and contact address of the manufacturer as required pursuant to Article 11 (5): Hikoki Power Tools Norway AS - MFT Postboks 124, 2027 KJELLER - Kjeller Vest 7, 2007 KJELLER
- **5.** System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 3**
- **6.** In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 14592:2008+A1:2012

Strojirenský zkusebni ústav, s.p. (SZU) Nr. 1015, has issued a certificate of conformity for production control in accordance with system 3, and determination of product characteristics.

7. Declared performance:

| Essential characteristics | Performance | | Characteristic density of wood $\rho_{k(kg/m^3)}$ | Harmonized technical specification |
|---|--|-------|---|------------------------------------|
| Characteristic yield moment M _{v.k} (Nmm) | Thread section | 3320 | | |
| Characteristic yield moment wy,k (willing | | | | |
| Characteristic withdrawal parameter f _{ax,k} | Loading across the fiber | 16,38 | 350 | EN 14592:2008+A1:2012 |
| (N/mm²) | Loading along the fiber | 13,62 | | |
| Characteristic head pull-through parameter | Countersunk head | 24,72 | 350 | |
| $f_{head,k}$ (N/mm ²) | Pan head | 330 | 330 | |
| Characteristic tensile capacity $f_{tens,k}$ (kN) | 4,89 | | | |
| Characteristic torsional ratio (kN) | 2,61 | | 450 | |
| Durability (i.e. corrosion protection) | Stainless steel A4, service class 3 acc.to-> | | | EN 1995-1-1 |



8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Kjeller, 30. August 2021

Vegard Haugen, Construction engineer MFT

Vegard Hayper